


Flooring BAMWOOD® range

Our "BamWood®" flooring is made from bamboo strips assembled under very high pressure, giving it a noble and elegant appearance. The planks are finished in the factory, either with a UV varnish with a matt appearance or with Woca® oil, also with a matt appearance. The quality of our products allows us to offer a warranty of up to 30 years on condition that the installation is done according to our instructions, respecting the norms in effect in the country and following our maintenance recommendations.




Champagne




Gold



Caramel



Nairobi



Corfou

Reference	Coating ¹	Color	Glued pose	Floating pose	Floor heating ³	Bath-room ³	Dimensions (mm)	Wear layer (mm)	Structure	Bevel	Inter-locking ²	Content box
F10BCC60	V	Caramel	✓	✓	✓	✓	10x60x920	±4	Solid	GO2	T/G	1,77m² 18kg
F10BIC200	B	Caramel	✓	X	✓	✓	10x200x300	±5	Solid	-	-	1,92m² 19kg
F10BCC130	V	Caramel	✓	✓	✓	✓	10x130x915	±4	Solid	GO2	T/G	1,9m² 19kg
F10BOC130	H	Caramel	✓	✓	✓	✓						
F10BCCH130	V	Champagne	✓	✓	✓	✓						
F10BOCH130	H	Champagne	✓	✓	✓	✓						
F10BCG130	V	Gold	✓	✓	✓	✓	10x95x855	±4	Solid	GO2	T/G	1,95m² 20kg
F10BOCBR95	H	Caramel	✓	X	✓	✓						
F10BOCHBR122	H	Champagne	✓	X	✓	✓						
F10BCCL125	V	Caramel	X	✓	X	X						
F10BCHCL125	V	Champagne	X	✓	X	X	10x125x920	±2,5	HDF	GO2	Click	1,38m² 12kg
F10BGCL125	V	Gold	X	✓	X	X						
F14BMCC190	V	Caramel	✓	✓	✓	✓	14x190x1850	±3	Multiply	GO2	Click	2,11m² 17kg
F14BMCCCH190	V	Champagne	✓	✓	✓	✓						
F14BMGCL190	V	Gold	✓	✓	✓	✓						
F12BCC142	V	Caramel	✓	✓	✓	✓	12x142x1850	±4	Solid	GO2	T/G	2,1m² 25kg
F12BOCH142	H	Champagne	✓	✓	✓	✓						
F12BCG142	V	Gold	✓	✓	✓	✓						
F12BCNA142	V	Nairobi	✓	✓	✓	✓						
F14BMCC142	V	Caramel	✓	✓	✓	✓	14x142x1850	±3	Multiply	GO2	T/G	2,1m² 21kg
F14BMCCCH142	V	Champagne	✓	✓	✓	✓						
F14BMCG142	V	Gold	✓	✓	✓	✓						
F14BMOC208	H	Caramel	✓	✓	✓	✓	14x208x1850	±3	Multiply	GO2	T/G	2,31m² 25kg
F14BMOCH208	H	Champagne	✓	✓	✓	✓						
F13BOCO140	H	Corfou	✓	✓	✓	✓	13x140x1850	±3	3 crossed layers bb	GO2	T/G	2,07m² 27kg
F13BONA140	H	Nairobi	✓	✓	✓	✓	13x140x1850	±3	3 crossed layers bb	GO2	T/G	2,07m² 27kg
F13BCNA140	V	Nairobi	✓	✓	✓	✓						

¹ V= varnish/ H= Oil / B= Unfinished - ² T/G = Tongue/Groove - ³ Installation on heated floor and in bathrooms **must be glued**.

Installation advice available on our website www.bambootouch.com/en/advice.

Storage, installation and maintenance (DTU 51.2 or local standard)

- Planks should be stored horizontally at a temperature of 15 to 25°C and relative humidity of 45 to 65 %.
- The flooring requires acclimatization and will be left 48h in its open packaging on the place of installation.
- Bamboo is a natural product. Variations in color, grain or shine are normal. Be sure to mix the planks from different packages before installation. **All installed flooring will be considered accepted.**
- The screed must be dry, clean and even. The moisture content, evenness and load-bearing capacity of the screed must be in accordance with current standards. Residual moisture must not exceed 2.7%.
- Allow for an expansion gap of +/- 1 cm around the floor and obstacles.
- Provide a divider joint every 8 to 10m.
- Splits and fiber separation are possible on oiled products. This phenomenon is natural and is no reason for warranty claim. A (light) sanding and oiling will reduce them.
- Blanchon® oil is not compatible with our oiled floorings.
- Installation, cleaning and maintenance instructions are available on our website www.bambootouch.com/en/advice.

Technical specifications

- Brinell hardness: ±9 kg/mm² (EN 1534 – CTIB 5229/2)
- Contraction coefficient: 0,14% per % of humidity variation
- Humidity level : 10% at 20° and 65% of relative humidity
8% at 20° and 50% of relative humidity
- Density : ±1.050 kg/m³
- Fire standard : CFLS1 if glued pose BFLS1 for some products
- Formaldehyde emissions: 0,04mg/m²h (EN 717-2 CTIB 5229/2)
- PCP level : below detection limit (CTIB 5229/2)
- VOC Free : below detection limit (EN15052 CTIB 5229/2)
- Thermal resistance : 0,05m²K/W (EN12664 CTIB 5229/2)
- Thermal conductivity : 0,20W/mK
- Warranty: up to 30 years under conditions (see our website)

nv Pi-Import sa

Av du Commerce 33

1420 Braine-l'Alleud – Belgium

Tel. : +32 (0)2 384 58 77

Technical File BamWood® flooring

info@bambootouch.com

www.bambootouch.com

